



## CA-N8708AS-P 8CH PoE Mini 1U Network Video Recorder



Save Storage



Mobile App



AI by Camera



PoE



HDMI Output



## Eco Series

- Up to 8 Channel IP camera input
- Supports IP cameras with up to **8MP (4K)** resolution
- Supports **8-Port PoE**
- Supports **1x SATA HDD**, up to 12 TB
- Up to **64Mbps** Incoming and **80Mbps** Outgoing Bandwidth
- Efficient Compression Technology H.265/H.265+/H.264/H.264+/MJPEG
- HDMI Output Supports Up to 4K Resolution
- Mobile App (iOS; Android)
- AI by Camera: Perimeter intrusion, Line Crossing, Object Detection, Pedestrian & Vehicle, Face Detection, Cross Counting, Sound Detection, Video Tampering, Cross Counting, intrusion, Enter Region, Exit Region, Schedule.



## I Specifications

Model Name		CA-N8708AS-P
Video		
IP Camera	Resolution	8MP, 5MP, 3MP ,2MP(1080P), 1.3MP(960P), 1.0MP(720P).
	IP Video Input	8-Channel
Recording Bandwidth	Incoming	64Mbps
	Outgoring	80Mbps
Performance		
Live/Playback	Compression	Audio: G.711a Video : H.264/H.265
	Frame rate	4K:30fps 4MP:60fps 2MP:120fps Multi display resolution 720P, Single channel up to 4K
	Event	MD(Sensitivity Level 1~8)
		Videlo loss Beep, Email, Push notification to Mobile APP
	Playback function	Fast forward / backward (2x, 4x, 8x,16x)
		Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 4CH Playback
	fisheye	Use WEB CMS,device does not support
Network	Protocal	ARP; DDNS; DHCP; DNS; Easy DDNS; HTTP; ICMP; IGMP; IPv4; IPv6; NTP; RTCP; RTP; RTSP; SSH; TCP/IP;UDP; Unicast; UPnP
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Mobile viewer	Yes
	Push Notification	P2P



Interface		
P/W Reset		YES
Monitors	VGA	1
	HDMI	1-port (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080, 1600*1200/1920*1200, 2560*1440, 3840*2160/EDID)
Connections	PoE	8-Port (RJ45), 802.3at/af
	Ethernet	1 RJ45 10/100 Base-T
	USB	2x USB2.0 (rear)
	HDD	1 SATA HDD, up to 12TB
AI Features		
	Smart Motion by Camera	SMD
		Perimeter intrusion, Line Crossing, Object Detection, Pedestrian & Vehicle, Face Detection, Cross Counting, Sound Detection, Video Tampering, Cross Counting, intrusion, Enter Region, Exit Region, Schedule
Alarm		
	General Alarm	Motion Detection, PIR, Combined Alarm, PTZ Linkage, Alarm Schedule, Deterrence, Siren, Alarm Disarm
	Exceptions Alarm	HDD Full, Disk Error, Video Loss
General		
System	OS	Embedded Linux
	OSD Language	English/French/Spanish/Portuguese/German/Italian/Greek/Danish/Finnish/Russia/Hebrew/Turkish/Bulgarian/Arabic/Korean/Japanese/Thai/Hindi/Romanian/Dutch/Polish
Third-party Camera Access		ONVIF, RTSP
Installation wizard		Yes
Mechanical design	Dimension (WxDxH)	230*215*47mm
Electrical	Input Voltage/Current	DC 48V/1A
	Power consumption (excluding hard disk)	4W
Environmental	Operating Temperature/Humidity	Temperature : 0°C~+50°C (32°F ~ 122°F) Humidity : Less than 90%RH



## Physical Interface



**CANADAI Co.,Ltd.**  
Smart Surveillance Systems  
Email us: [Support@Canadai.net](mailto:Support@Canadai.net)



\*All pictures and specifications are for reference only  
And are subject to change without prior notice.